

Product Data Sheet

Model identifier(s):	RA 3737					
Item	Symbol	Value	Unit	Item	Unit	
Heat output				Type of heat input, for electric storage local space heaters only		
Nominal heat output	P_{nom}	1,400	kW	manual heat charge control, with integrated thermostat	N / A	
Minimum heat output (indicative)	P_{min}	0.00	kW	manual heat charge control with room and / or outdoor temperature feedback	N / A	
Maximum continuous heat output	$P_{max,c}$	1,400	kW	electronic heat charge control with room and / or outdoor temperature feedback	N / A	
Auxiliary electricity consumption				fan assisted heat output	N / A	
At nominal heat output (fan motor)	el_{max}	N / A	kW	Type of heat output / room temperature control		
At minimum heat output (fan motor)	el_{min}	N / A	kW	single stage heat output and no room temperature control	no	
In standby mode	el_{SB}	N / A	W	Two or more manual stages, no room temperature control	no	
				with mechanic thermostat room temperature control	yes	
				with electronic room temperature control	no	
				electronic room temperature control plus day timer	no	
				electronic room temperature control plus week timer	no	
				Other control options		
				room temperature control, with presence detection	no	
				room temperature control, with open window detection	no	
				with distance control option	no	
				with adaptive start control	no	
				with working time limitation	no	
				with black bulb sensor	no	
Contact details	Clatronic International GmbH, Industriering Ost 40, 47906 Kempen / Germany					